



AJAX

Tech specs

LeaksProtect

Classification Radio channel water leak detector

Type of detector Wireless

Installation method Indoors

Compatibility Operates with all Ajax Hubs and Range Extenders

Alarm signal delivery time 0.15 s

Power supply Battery: Two AAA batteries, 3 V

Battery life Up to 5 years

Jeweller radio technology Communication range with central unit – up to 1,300m in an open space
Two-way communication between devices

Radio frequency bands (depends on the region of sale):

866.0 – 866.5 MHz

868.0 – 868.6 MHz

868.7 – 869.2 MHz

905.0 – 926.5 MHz

915.85 – 926.5 MHz

921.0 – 922.0 MHz

Self-adjusting RF output power – up to 20 mW

Block encryption based on AES algorithm

Detector polling period – 12–300 s



Tech specs

LeaksProtect

Temperature sensor	Available
Operating temperature range	From 0°C to +50°C
Permissible humidity	Up to 100%
Anti-sabotage	Protection against fraud Jamming detection
Protection class	IP65
Remote setting and testing	+
Dimensions	56 x 56 x 14 mm
Weight	40 g
Warranty	Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty
Complete set	LeaksProtect leak detector Two AAA batteries (pre-installed) User's guide