

Fixed Temperature Heat Detector FD8010

Rate of Rise Heat Detector FD8020



The fire detectors FD8010 and FD8020 provide reliable early warning of a fire condition upon ambient temperature reaching a fixed temperature threshold. They are available in two versions (A2S or BS for FD8010 and A2R or BR for FD8020) depending on the temperature threshold in accordance with the European Standard EN54-5.

The fire detectors are suitable for premises with normal or high ambient temperature, with possible sudden changes.

AVAILABLE 2000 RAL
COLOURS UPON REQUEST

Technical data

Supply voltage:

– (10-30) VDC

Duty mode current:

– 44 μ A / 24 Vdc

Fire condition current:

- with base type 8000 or 8000D: (8-25) mA
- with base type 8000R, 8000DR: (18-55) mA

Terminals:

- For wires with cross section (0.5-2.5) mm²
- Degree of protection: IP 43

Operation temperature: -10 °C to +55 °C

Relative humidity: (93 \pm 3) % at 40 °C

Sensitivity and temperature class: In accordance with EN54-5, class A2S or BS for FD8010 and class A2R or BR for FD8020

Mounting: Using bases of series 8000

Dimensions (base included): \varnothing 100, h 47 mm

Casing material: ABS plastics, white

Weight (base included): 0.100 kg

Protected area: Circle with diameter 10m, h 8m



Office building UniPOS,
1 Efr. Nikola Paskalev Str., Mladost 1, Sofia 1748, Bulgaria
Phone: +359 2 97 439 25, +359 2 97 444 69

47 San Stefano Str., Pleven 5800, Bulgaria
Phone: +359 64 891 100

www.unipos-bg.com